

Rider-M - Series Scrubbers

DUAL DISK		CYLINDRICAL	
			
28 in / 810 mm	32 in / 813 mm	26 in / 710 mm	30 in / 762 mm

Tank Material:	Poly 5/16" (7.9mm)		
Chassis Construction:	3/16" Steel (4.8mm) Powder Coated Steel		
Front Wheels (Diameter x Width):	10" x 3" (25 x 7cm) - Non-Marking Grey		
Rear Casters (Diameter x Width):	12 x 3" (6.4 x 3.5cm) - Non-Marking Grey		
Length x Width x Height	67 x 37 x 60 in *		
<small>*Dimensions listed are for the largest width deck configuration and squeegees removed from the machine</small>	170 x 94 x 152 cm*		
Scrub Motor(s):	(2x) 0.75 hp / 559 watts		
Brush RPM:	270 rpm		
System Voltage:	24 VDC		
Standard Battery:	240ah WET		
Battery Run Time:*	Up to 4 Hours		
Charger:	Onboard CE & CEC 27A		
Traction Drive System:	0.75hp - All Gear / Sealed (559 watts)		
Solution Tank Capacity:	40 gal / 151 L		
Solution Flow / Filter:	0 - 0.6 GPM / Stainless Inline (0 - 2.3 LPM)		
Recovery Tank Capacity:	42 gal / 159 L		
Vacuum Motor:	0.8 hp / 24V / 3 Stage / 640 watts		
Vacuum Water Lift:	70" / 178 cm / 70 cfm		
Squeegee:	37 in (94 cm)	41 in (104 cm)	41 in (104 cm)
Sound Levels:**	66 dBA**		
Productivity - Theoretical:***	38,500 ft ² /hr 3,576 m ² /hr	44,000 ft ² /hr 4087 m ² /hr	35,750 ft ² /hr 3,321 m ² /hr
Productivity - Practical:***	18,000 ft ² /hr 1,672 m ² /hr	20,500 ft ² /hr 1,904 m ² /hr	16,000 ft ² /hr 1,579 m ² /hr

Location:
 Timberline Cleaning Equipment
 1711 South Street
 Racine, WI
 53404

Phone:
 877-401-0730

Email:
customerservice@timberlineclean.com
Website:
www.timberlineclean.com

Specifications subject to change without notice.
 *Battery Run Times are based on continuous scrubbing run times, standard batteries, low down pressure and all options off.

**Decibel levels for Disk per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

***Productivity is based off of ISSA 2010 Cleaning Times